



# **DeckTape**° 50MM-300MM Range









**50MM** 



AVAILABLE IN 8 DIFFERENT WIDTHS!



**82MM** 

65MM

100MM





300MM

## What will your deck frame look like in 5 years?

150MM

Protect your joists with DeckTape





### ADVANCED 5-LAYER TECHNOLOGY®

- **UV & WATERPROOF LAYER**
- ② ULTRA HIGH STRENGTH WEAVE **UV & WATERPROOF LAYER**
- SPECIALIST PMMA ADHESIVE











**AVAILABLE IN STORE AND ONLINE** 















### **Curing Process:**



### Coloured water test:



DeckTape® becomes gradually stronger over 24-72 hours as the adhesive soaks into the timber and fully cures.

Completely self-sealed when fastener is driven through the DeckTape®

**50MM X 20M** 

[top of single joists]



65MM X 20M

[top of single joists]



82MM X 20M

[noggins]



100MM X 20M

[ top of double joists ]



150MM X 20M [top of triple joists]



200MM X 20M

specialised applications



250MM X 20M



300MM X 20M [joists below curved decking]



## Completely protects and seals your new or existing timber deck frame from water/moisture rot and frame weathering.

- Non-Butyl & easy-to-tear
- Completely UV Stable
- Self-Seals Around Fasteners
- Permanent Adhesive Bond For 50 Years
- Made with sustainable & recycled materials
- Can Apply to Damp Timber or Below Freezing









