

**Applications:**

- Temporary protection of all smooth and porous surfaces
- Protection of sills, windows, ornaments etc during sandblasting, painting, plastering and grinding
- Protection of vulnerable parts during renovation and repair work
- Protection against scratching of finished products during transportation or temporary storage.

Walther Strong Interior Liquid Tape is a water-based yellow-transparent gel that after drying forms a strong and flexible, easily removable foil that offers good protection against scratches, paint, plaster, cement, PU foam etc.

Interior Liquid Tape can be used with both renovation and new construction work in industrial or automotive applications.

The foil has good adhesion to practically all surfaces and does not slip. When the work is done, the flexible membrane can be very simply pulled off the surface.

Apply on a dry and clean surface with a brush, roller or airless spraying device (nozzle type 625 - remove filters). Always remove the product as soon as the job is completed. The sooner the better. The thicker the layer, the simpler to remove.

Apply on a clean dry surface using a brush, roller or airless spray gun. Consumption: apply at least 500ml/m<sup>2</sup> (0.5mm thickness) in one coat. Apply from 10°C. Only suitable for indoor use.

Drying time of 2 - 4 hours at 23°C/50% RV. Clean tools before the product dries with water.

Remove within 3 months. Always test the surface/substrate first. The product should not be used on sandblasted timber and/or fabrics.

Please test the product on delicate surfaces. Do not apply in direct sunlight. Do not leave in direct sunlight. For **interior** use only.

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008. This mixture does not contain any notifiable substances. Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed.

Remove waste in accordance with local and/or national regulations. Safety data sheet available upon request. For further technical, safety advice and details please contact the Walther Strong team.

