

Section 1 - Identification of The Material Manufacture

Company Details:

Walther Strong & Company Ltd
Unit 3, Dysart Road
Autumn Business Park
NG31 7DD

Phone: 01780 437222

Website: www.waltherstrong.com

Email: enquiries@waltherstrongandco.com

Section 2 - Product Description

General purpose multi-surface tape ideal for everyday construction tasks that require heavy duty strength.

Tackle a wide range of construction and DIY tasks with our heavy duty Double-Sided Tape, engineered for strength, versatility, and instant performance. Designed for both permanent bonds and temporary applications, this tape delivers a powerful instant grip you can rely on across countless projects.

PRODUCT CODE	PRODUCT DESCRIPTION	BOX QTY
TP-MPDS25X5PR	25MM X 5M	10
TP-MPDS50X5PR	50MM X 5M	10

Section 3 - Key Features

- Strong adhesive for a secure, lasting bond
- Can be used for mounting with it's strong holding power
- Ideal for temporary tiling
- Strong adhesive
- Powerful instant grip
- Can be used on smooth and uneven surfaces

Section 4 - Application

Foam tapes are used for electrical cables bundling, colorcoding, duct sealing, general purpose splicing, hardnessing, hand application.

Section 5 - Technical Data

PROPERTIES	UNIT	TOLERANCE	TEST METHOD
Thickness of tape	mm	1 ± 10%	INITIAL
Weight of tape	gr/m ²	135 ± 10%	INITIAL
Weight of liner	gr/m ²	78 ± 10%	INITIAL
Thickness of liner	micron	70 ± 10%	INITIAL
Adhesion on steel	N/25mm	≥ 16	PSTC - 101
Tack (φ11 Ball)	cm	<10	PSTC - 6
Shear at 23 °C	hr	<5	PSTC - 107
Temperature resistance	°C	(-20)°C / (+120)°C	

Section 6 - Shelf Life & Storage

Recommended shelf life of the product is 12 months. Jumbo or Finished Rolls on verticle position stored without direct sun contact and in room temperature of 21°C and humidity of 50%.