

Section 1 - Identification of The Material Manufacture

Company Details:

Walther Strong & Company Ltd
Unit 3, Dysart Road
Autumn Business Park
NG31 7DD

Phone: 01780 437222

Website: www.waltherstrong.com

Email: enquiries@waltherstrongandco.com

Section 2 - Product Description

Walther Strong Interior Clean Room Construction Tape is uniquely designed to meet the needs of professional contractors. The tape has a specialist adhesive which is designed to remove cleanly from internal hard and soft surfaces. It is a replacement to duct tape but leaves no residue.

Walther Strong Interior Clean Room Construction Tape is designed for critical environment construction and support applications. It can also be used for floor marking, colour coding and delicate sealing to protect important surfaces. It has a high adhesion level but good cohesive strength, leaves no residue and is resistant to acids and other chemicals.

A replacement to clamps, nails and screws for joinery applications.

Tip: Our Interior Clean Room Construction Tape is ROHS certified and meets COSH regulations. The tape is manufactured with an embossed pattern which has the benefit of NO marks being left by this technologically advanced product, and tears straight. (Always test on the surface first)

PRODUCT CODE	PRODUCT DESCRIPTION	BOX QTY
CR-ORN50X33/1	50MM X 33M	24

Section 3 - Applications

- The replacement to duct tape
- Used as a temporary protection in renovation projects
- Electrical insulator >600V
- Taping for temporary protection on flooring
- Unique easy tear, ideal for decorators
- Replacement to clamps, nails and screws
- Ideal for masking aluminum, UPVC and painted wooden window and door frames

Section 4 - Technical Performance

DESCRIPTION	UNITS	VALUE	METHOD
Tape thickness	mm/mils	0.160 / 6.3	ASTM D-1000
Adhesion to steel	kg/cm, oz/in	0.10 / 8.8	ASTM D-1000
Elongation at break	%	110	ASTM D-1000
Tensile strength	kg/cm, lbs/in	1.6 / 8.8	ASTM D-1000

Section 5 - Storage

Shelf life recommended one year from the date of dispatch at the moderate temperature and humidity environment.

NOTICE: Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.