

## Section 1 - Identification of The Material Manufacture

### Company Details:

Walther Strong & Company Ltd  
Unit 3, Dysart Road  
Autumn Business Park  
NG31 7DD

**Phone:** 01780 437222

**Website:** [www.waltherstrong.com](http://www.waltherstrong.com)

**Email:** [enquiries@waltherstrongandco.com](mailto:enquiries@waltherstrongandco.com)

## Section 2 - Product Description

Walther Strong Drylining HD Scrim is a high strength white fibreglass mesh tape designed to reinforce plaster coatings and prevent cracking. With an extra long 180m roll, it is perfect for large scale projects and is fully compatible with scrim tape guns such as the Marshalltown MT72, enabling fast, efficient application.

Built for professional dryliners, this heavy duty scrim tape features a strong adhesive that stays firmly in place and performs reliably in both hot and cold environments. It has been successfully used in projects ranging from castle renovations to office blocks and skyscrapers, delivering a clean, durable, and professional finish every time.

Used successfully in a variety of challenging projects, including historical restorations, office buildings, and skyscrapers, Walther Strong Drylining HD Scrim ensures reliable results, project after project.

### Why Choose Walther Strong Drylining HD Scrim?

Designed for professional dryliners, this tape combines durability, ease of use, and high performance reinforcement. Ensure plaster coatings remain strong, crack-free, and long lasting with Walther Strong.

| PRODUCT CODE     | PRODUCT DESCRIPTION | BOX QTY |
|------------------|---------------------|---------|
| TP-XLSCRIM50X180 | 50MM X 180M         | 12      |

## Section 3 - Key Features

- Strong fibreglass scrim tape for drylining joint reinforcement
- Helps support long lasting crack resistance
- Dual adhesive system for superior grip
- Ideal for large scale projects, reducing downtime
- Professional results in cold and hot site conditions
- Compatible with the Marshalltown MT72 gun - Please call in to source the gun
- Specialist ALKAMAXX coating for alkali resistance

**Section 4 - Technical Data**

| PROPERTIES                                      |              | MATRIC       | IMPERIAL     | ASTM   |
|---|--------------|--------------|--------------|--------|
| Construction: (per 100mm)                       | Warp<br>Weft | 36<br>36     | 9<br>9       | D-3775 |
| Weight: (g/m <sup>2</sup> - ozyd <sup>2</sup> ) |              | 63.1 +/- 2.2 | 1.85 +/- 0.1 | D-3776 |
| DPU (Coating and PSA on fabric in weight %)     |              | 40-45%       | 40-45%       | SGTF   |
| Thickness: (per mm - per inch)                  |              | 0.3          | 0.01         | D-1777 |
| Tensile Strength: (N/2.54cm - lbs/in)           | Warp<br>Weft | 228<br>470   | 50<br>105    |        |

**Section 5 - Storage**

Store between 8-30°C. Do not use if left in a van overnight in cold weather. Remove, bring to room temperature (minimum 15°C) before using if cold weather. Avoid frost.